



LCD MONITOR

Display size	19" (48,26 cm)
Panel Type	Active Matrix TFT
Brightness	300 cd/m ² (typ.)
Contrast	1000:1 (typ.)
Pixel pitch	0,294(H) x 0,294(V) mm
Resolution (H x V)	SXGA 1280 x 1024
Response time	5 ms (typ.)
View angles LR,UD	H/V 170°/160°
Display colors	16,2 Mio colors
Display Surface	Anti-Glare
Input 1	VGA, Audio
Input 2	DVI-D
Input 3	
Headphone	
Speakers	1W x 2
Supply	AC 100~240V, 50~60Hz
Consumption	37 W (typ.)
Temperature	5 ~ 35°C
Humidity	10 ~ 85%
Dimension (W*D*H)	416 x 203 x 413 mm
Net weight	5,7 kg
Tilt	0°~ 20°
Kensington Lock	✓
VESA mounting	VESA Standard, 100mm
On screen display	EN, SC, TC, DE, FR, IT, ES, JS
Safety	UL/CUL, TUV, CB, BSMI, FCC, CE, GOST
Emission	TCO03
Power saving	EPA Energy Star
Extras 1	
Extras 2	
Extras 3	
EAN	4710859553577
incl Accessory	powercord, VGA cable, audio cable, users manual (CD), quickstart guide (paper), warranty card

© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.

The specifications are valid from production year 2008